

# פנס חכם מבוסס לד Robe- FORTE



## ROBE

ה- FORTE החדש של ROBE, פנס חזק במיוחד, עוצמתי (מייצר אלומת אור איכותית בעוצמת הארה של 150,000lm!!!!) ומסוגל לשמור על עוצמת האור לאורך זמן בזכות TE (transferable engine) שפותח ב-ROBE, זום של 5°-55°, CMY, גוביום, בלי HOTSPOT, טכנולוגיית Cpulsen, ועוד...

### מפרט טכני

כללי

יצרן: Robe

צבע גוף: black

חשמל

מתח עבודה: 100V-240V, 50/60 Hz

הספק כולל: 1200W

מקור אור

סוג נורה: E™ 1.000W White LED TRANSFERABLE ENGINE

עוצמת הארה: L70/B50 @ 50.000 hours

אורך חיי נורה: min. 50.000 hours

גוון צבע: 6.700K

CRI: 70/80/90, remotely selectable

זווית פיזור: 5° - 55°

מידות

רוחב: 483.5mm

גובה: 843mm

עומק: 288.5

משקל: 39.5Kg

## שליטה

USITT DMX-512, RDM, ArtNet, MA Net, MA Net2, sACN, Webnet: שליטה  
Wireless CRMX™ technology from Lumen Radio: On request: שליטה אלחוטית:  
**DMX:** 1mode, 54 channels מצבי הפעלה

## קירור

טמפ' עבודה: -5°C-45°C

## סביבת עבודה

דירוג IP: IP20

## פרמטרים Moving Light

איריס: Motorized, stepless, pulse effects up to 3 Hz

פרוסט: Light 1° for instant softening of the projected gobo and framing shutters and medium 5° for even wash, both frosts replaceable via magnetic holder

פוקוס: Motorized focus

Zoom: Motorized zoom

CMY / RGBW: CMY | CTO

גלגל גובו 1: rotating, indexable and replaceable breakup and aerial gobos + open, patented slot & lock 6 system

גלגל גובו 2: rotating, indexable and replaceable breakup and aerial gobos + open, patented slot & lock 6 system

גלגל צבע 1: fixed dichroic colours+ white 5

גלגל צבע 2: replaceable + white 5

פריזמה: prisms : linear and circular: 6 facet prism rotating in both directions at variable speed 2

גלגל אנימציה: Aluminium animation wheel, used alone or in combination with gobos, rotating in both directions at variable speed

שאטר: Patented framing shutters module with 4 individually positionable blades plus rotation of the complete frame system +-60°

סטרובו: Electronic strobe effect with variable speed up to 20 Hz, pre-programmed random strobe & pulse effects

תנועה: Pan movement: 540°# Tilt movement: 270°# EMS™: Electronic Motion Stabilizer system for Pan &

(Tilt reducing beam deviation caused by truss movement or vibration (Patent pending

**(HOTSPOT:** Hot-Spot: From flat field to 6:1 hot-spot (optional

**Robe FORTE**

לחץ לצפייה בRobe FORTE

