



High Power LED Linear Wall Washer



LED Colour Temperature


- 2000K
- 3000K
- 6000K

Optics



B33(B33D/B33F)	
L0109F023YH	9°
L0115D023YH	15°
L0120D023YH	20°
L0130D023YH	30°
L0145D023YH	45°

B33(B33D/B33F)



Optional Honeycomb Louver



Air Valve



Cap-Optional Accessory




Adjustable beam direction


Outer Dimensions

Unit:mm

Low voltage input (24VDC)




B6QB1057




B6QB2057

High voltage input (100V-240V)



B6QC1057




B6QC2057


Material specifications

Housing	Extruded aluminum, powder coated
Lens	Optical lens, efficiency 285%
Light Window	Tempered glass, T=3mm
Cable gland	IP68 PG-11 PA66
Seal	Glass and housing are silicone sealed
LED	OSRAM SMD 3535
Operating temperature	-20°C~40°C
Bracket	12# Die-casting powder coated aluminum
Power Cable	H05RN-F 2X1.5mm ² L=0.25m (low voltage) H05RN-F 3X1.0mm ² L=0.5m (high voltage)
Dimmable support	Triac PWM 1-10V Dali (B6QB1057/B6QB2057)

Low voltage input (24VDC) power cord model






High voltage input (100V-240V) power cord wiring model






Item	Light source	Lens	The manufacturer selected lens degree(°)θ1/2	Length L=(mm)	Input voltage(V)	Typical operating current(mA)	Typical consumption(W)	Typical luminance(lm)	IK rate
B6QB1057	10×2W Single color	B33D	20°	525	24V DC	1041	25.0	Cool white =1476 Warm white =1174	05
B6QB2057	20×2W Single color	B33D	20°	1025	24V DC	2056	50.0	Cool white =2890 Warm white =2308	05
B6QC1057	10×2W Single color	B33D	20°	525	120/240	120V = 174 240V = 92	120V = 20.8 240V = 20.8	Cool white =1476 Warm white =1338	05
B6QC2057	20×2W Single color	B33D	20°	1025	120/240	120V = 374 240V = 202	120V = 41.0 240V = 42.2	Cool white =2890 Warm white =2518	05

B6QB1057 B6QC1057



Distance (m)	Center beam LUX	Beam width V (m)	Beam width H (m)
2m	1519.48	0.8m	0.8m
4m	379.87	1.6m	1.7m
6m	168.83	2.5m	2.5m
8m	94.97	3.3m	3.3m
10m	60.78	4.1m	4.1m
12m	42.21	4.9m	5.0m

B6QB2057 B6QC2057



Distance (m)	Center beam LUX	Beam width V (m)	Beam width H (m)
2m	3343.99	0.8m	0.8m
4m	836.00	1.6m	1.6m
6m	371.65	2.3m	2.3m
8m	209.00	3.1m	3.1m
10m	133.76	3.9m	3.9m
12m	92.89	4.6m	4.7m