פנס מבוסס לד
Robe - IESPRITE

IESPRITE מצטרף לפנסי Robe מוגני המים, פנס המשלב את הטכנולוגיה העדכנית של הESPRITE המוכר והאהוב עם דרגת IP65.

עם גודל, צורה ומשקל דומה למקבילו (34 קילו בלבד!)\ ושילוב כל התכונות של ESPRITE, מאפשר אינטגרציה חלקה בין הדגמים.

מערכת ההגנה של הפנס מאפשרת פעולות אחזקה שונות כמו החלפת מנגנון הTE והחלפת גובואים בצורה פשוטה וללא פגיעה במערכת המיגון של הפנס.

מערכת זום זהה עם 5.5°-50°, מערכת CMY וCTO- עם מעבר חלק בין הצבעים, ארבעה שאטרים, גלגל אנימציה, ועוד...

תואם האופן מלא למערכת Robospot.

מפרט טכני

כללי

יצרן: Robe

צבע גוף: Black

חשמל

מתח עבודה: 100-240 V, 50/60 Hz

הספק כולל: Standard mode max. 870 W at 230 V / 50 Hz | High-power mode max. 950 W at 230 V / 50 Hz

מקור אור

סוג נורה: (Light source type: TE-iSE™ 650W HP White LED Engine (patented

עוצמת הארה: (LED Engine output: 55.000lm# 34,000lm (integrating sphere)# 27,000lm (goniophotometer

אורך חיי נורה: 50,000h

גוון צבע: 6700K

CRI: CRI 70, remotely selectable filters for CRI 80 and CRI 90

זוית פיזור: 50° - 5.5°

מידות

רוחב: 458mm

גובה: 756mm

עומק: 289mm

משקל: 34Kg

שליטה

שליטה: USITT DMX-512 | RDM | ArtNet | MA Net | MA Net2 | sACN

שליטה אלחוטית: Wireless CRMX™ technology from Lumen Radio

מצבי הפעלה **DMX:** Control channels: 49, 42, 50, 43

העמסות

רעש: (dB(A) at 1 m (quiet mode) | 42 dB(A) at 1 m (auto mode 27

קירור

טמפ' עבודה: -50°c-50°

סביבת עבודה

דירוג **IP:** IP65

פרמטרים Moving Light

איריס: Motorized, stepless, pulse effects up to 3 Hz

פרוסט: MagFrost™ - magnetic paddle fast change system providing exchangeable frosts containing as standard a very light 1° for instant softening of the projected gobo or framing shutters, and a medium 5° for even wash, both specifically selected for theatre and TV use

פוקוס: Motorized zoom and focus

Zoom: 5°-50°

CMY / RGBW: Cyan: 0 - 100%# Magenta: 0 - 100%# Yellow: 0 - 100%# Variable CTO: 3.000K - 6.700K# +

- Green correction function

גלגל גובו 1: 7 rotating, indexable and replaceable breakup and aerial gobos + open, patented slot & lock system

גלגל גובו 2: 9 static and replaceable gobos + open

גלגל צבע 1: 5 fixed dichroic colours + white

גלגל צבע 2: 5 fixed dichroic colours + white

פריזמה: 6-facet prism rotating in both directions at variable speed

גלגל אנימציה: Aluminium animation wheel, used alone or in combination with gobos, rotating in both directions at variable speed

שאטר: Patented Plano4™ framing shutters module with 4 individually positionable blades plus rotation of the complete frame system + - 60°

סטרוב: Electronic strobe effect with variable speed up to 20 Hz

תנועה: Pan movement: 540°# Tilt movement: 265°# Movement control: Standard and Speed# EMS™: Electronic Motion Stabilizer system for Pan & Tilt reducing beam deviation caused by truss movement or vibration (Patented)# Automatic Pan & Tilt position correction# MAPS™ - Motionless absolute positioning (system for Pan and Tilt (Patented

(**HOTSPOT:** from flat field to 6:1 hot-spot (optional

⊕ נתונים נוספים

נתונים נוספים: Display: QVGA Robe touch screen with battery backup, gravitation sensor for auto screen positioning, operation memory service log with RTC, stand-alone operation with 3 editable programs (each up to 100 steps), built-in analyser for easy fault finding, NFC app controller# Epass™: Ethernet pass through switch which sustains Ethernet integrity, when the fixture has no power, to automatically maintain network connectivity# RAINS™ (Robe Automatic Ingress Neutralization System) manages humidity, temperature and pressure control using an active monitoring system to automatically remove any moisture detected within the fixture and provides constant monitoring to ensure peak performance# L3™ - (Low Light Linearity) Imperceptible 18 bit dimming for ultra smooth fade to black# Cpulse™ special flicker-free management for HD and UHD cameras, ready for 8K and 16K# AirLOC™ (Less Optical Cleaning) technology greatly reduces the level of airborne particles drawn over the optical elements. This increases the overall performance, light quality and time between routine cleaning and maintenance.# POLAR+™ for #power saving and instant operation in extremely cold weather conditions

---

קבצים להורדה

דף מידע
(kB 914.05)

טבלאת DMX
((849.57 kB

מידות
(kB 334.08)